



**PETRONAS**

## TECHNICAL CHARACTERISTICS

**SELENIA K P.E.**

**PRODUCT CODE: 1411**

### APPLICATION

Synthetic lubricant designed for the latest generation, low emission, petrol engines. Its specific formulation warrants the utmost protection also of high performance turbocharged engines with high thermal stress. Its low ash content helps to maintain the total cleanliness of modern catalysts.

### SPECIFICATIONS

SAE 5W-40, ACEA C3, API SN/CF,  
FIAT 9.55535-S2 CONTRACTUAL TECHNICAL REFERENCE N°F603.C07, MB-Approval 229.51,  
VW 502.00-505.00, VW 505.01, BMW LL-04

### TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY AT 15°C	ASTM D4052	g/cm <sup>3</sup>	0,850
VISCOSITY AT 100°C	ASTM D445	cSt	14
VISCOSITY INDEX	ASTM D2270	--	175
FLASH POINT CI. O. C.	ASTM D92	°C	> 200
T.B.N.	ASTM D2896	mg KOH/g	> 7
POUR POINT	ASTM D97	°C	<-33

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

08/2016