

Silicone spray

Ensures long-lasting protection, preservation and insulation of vehicle exterior and interior plastic, rubber and metal parts; good lubricating properties

- Plastic parts retain a high-gloss finish and do not become brittle
- Rubber parts are protected, do not become brittle and do not freeze or stick
- Impregnated folding roofs and hoods
- Anti-static effect (dust-repellent)
- Protects electrical contacts against moisture
- Sliding roof and seat rails, seat belt rollers etc. run smoothly
- Prevents squeaks and creaks between dissimilar materials,
 e.g. metal/plastic etc.
- Serves as an installation aid, e.g. for hose connections
- No staining

Chemical basis	Mineral oil
Min./max. temperature conditions	-5 to 40 °C



Contents	Container	Shelf life from produc- tion	Density/conditions	Art. no.	P. Qty.
5 l	Canister	24 Month	0.74 g/cm³/at 20°C	0893 221 05	1
20	Canister	12 Month	0.735 g/cm³/at 20°C	0893 221 520	1
500 ml	Spray can	24 Month	0.61 g/cm ³ /at 20°C	0893 221	1/12/24

The usage instructions are recommendations based on the tests we have conducted and are based on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products for	Designation	Art. no.
	Tap Tap for 5 L plastic canister	0891 302 01
0893 221 05	DN 60 tap Plastic tap with DN 60 connection for 20-l plastic canister and 60-l plastic drum	0891 302 03
	Filling system REFILLO®	0891 800 14
	Filling can REFILLO®mat	0891 881 12
	Refillo® compressed-air filling station Combi	0891 800 001
0893 221 520	Tap Tap for 5 L plastic canister	0891 302 01
	DN 60 tap Plastic tap with DN 60 connection for 20-l plastic canister and 60-l plastic drum	0891 302 03
	Filling system REFILLO®	0891 800 14
	Filling can REFILLO®mat	0891 881 12
	Canister coating ORSY®protec	0891 870 77