

## COMBINATION FILLING UNIT



<b>Art. No.</b>	<b>0986 02</b>
<b>P.</b>	1
<b>For 25 kg grease drums</b>	300-335 mm
<b>Cover diameter</b>	365 mm
<b>Height</b>	535 mm

Supplement to Art. No.:	Designation	Art. No.
0986 02	Central lubricating system filling hose	<b>0986 021</b>

### Note

Common greases up to NLGI Class 2 can be used. We expressly exclude any other use.

Lube-Shuttle® is a registered trademark of MATO GmbH & Co KG.

**Filling unit for professional, economical and clean working with lubricating greases**

### Suitable for filling:

- Lube-Shuttle system cartridges in conjunction with refill adapter
- Hand-Lever Grease Guns
- One-Hand Guns
- Lubricating units with filling nipple in accordance with DIN 1283.

### Application

The combination filling unit is suitable for filling Lube-Shuttle® system cartridges in conjunction with refill adapters, hand-lever grease guns, one-hand guns and lubricating units that are fitted with a lubricating nipple in accordance with DIN 1283, with standard greases up to NLGI Class 2.

## HAND-LEVER GREASE GUN



<b>Art. No.</b>	<b>0986 00</b>
<b>P.</b>	1
<b>Material</b>	ST    Steel
<b>Length</b>	370 mm
<b>Operating pressure</b>	400 bar
<b>Max. operating pressure</b>	800 bar

Scope of delivery for Art. No.	Designation	Art. No.	Quantity
<b>0986 00</b>	Reinforced Rubber Hose	<b>0986 002</b>	1
	Mouthpiece	<b>0986 003</b>	1

Supplement to Art. No.:	Designation	Art. No.
0986 00	Metal feed piece	<b>0986 001</b>

**For 400 g cartridges (DIN 1284, 235 x dia. 53.5 mm) or for 500 cm<sup>3</sup> of loose grease**

- For 500 cm<sup>3</sup> of loose grease, 400 g cartridges (235 x 53.5 mm dia.)
- Feed quantity can be metered up to 1.5 cm<sup>3</sup>
- Working pressure 400 bar
- Maximum pressure up to over 800 bar
- Actuating force 50 to 330 N with feed pressures from 50 to 400 bar
- Complies with DIN 1283 (M10x1) and is TÜV/GS, BLT and DLG-tested.
- Delivery: with reinforced rubber hose and a mouthpiece (M10x1)

This information is only a recommendation based on our experience. Preliminary testing required! When using the product, both the technical data sheet and the specifications of the applicable regulations must be complied with.