

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 18/12/2018 Revision date: 18/12/2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : WYNN'S INJECTOR DECARBONIZER 500ML

Product code : 14355

Type of product : Aerosol, Cleaner, Detergent

Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

WYNN'S BELGIUM B.V.B.A. Industriepark West 46 B-9100 Sint-Niklaas - Belgium T +32 3 7666020 - F +32 3 7781656

www.wynns.com

1.4. Emergency telephone number

Emergency number : BIG: +32 (0) 14/58.45.45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

H222·H229 Aerosol, Category 1 Acute toxicity (inhalation:dust,mist) Category 4 H332 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Specific target organ toxicity — Single exposure, Category 3, H335 Respiratory tract irritation Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 Specific target organ toxicity — Repeated exposure, Category 2 H373 Hazardous to the aquatic environment — Acute Hazard, Category 1 H400 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :









GHS02

GHS07

GHS08

GHS09

1/10

Signal word (CLP) : Danger

Hazardous ingredients : acetone; propan-2-one; propanone; benzyl alcohol; AROMATIC HYDROCARBONS, C8

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness.

H373 - May cause damage to organs through prolonged or repeated exposure (if inhaled).

H410 - Very toxic to aquatic life with long lasting effects.

18/12/2018 (Version: 1.0) EN (English)
18/12/2018 (Version: 1.0)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe spray.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTRE or doctor if you feel unwell. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	25 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
AROMATIC HYDROCARBONS, C8	(CAS-No.) 90989-38-1 (EC-No.) 292-694-9	25 - 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5	10 - 20	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302
ISOTRIDECANOL, ETHOXYLATED	(CAS-No.) 69011-36-5 (EC-No.) 931-138-8	2,5 - 3	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
HYDROCARBON WAXES (PETROLEUM), OXIDIZED	(CAS-No.) 64743-00-6 (EC-No.) 265-205-1	< 2,5	Eye Irrit. 2, H319
1,3-butadiene; buta-1,3-diene	(CAS-No.) 106-99-0 (EC-No.) 203-450-8 (EC Index-No.) 601-013-00-X	< 0,1	Flam. Gas 1, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact

: Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label).

18/12/2018 (Version: 1.0) EN (English) 2/10



18/12/2018 (Version: 1.0)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes damage to organs.

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing

dust/fume/gas/mist/vapours/spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Use only outdoors or in a well-ventilated area. Avoid breathing

dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.

: Strong bases. Strong acids.

Incompatible products Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone; propan-2-one; propanone (67-64-1)		
Germany TRGS 900 Local name		Aceton
Germany TRGS 900 Occupational exposure limit value (mg/m³) 1200 mg/m³		1200 mg/m³
Germany TRGS 900 Occupational exposure limit value (ppm)		500 ppm

18/12/2018 (Version: 1.0) EN (English) 3/10 18/12/2018 (Version: 1.0)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone; propan-2-one; propanone (67-64-1)		
Germany	TRGS 900 Limitation of exposure peaks	2(I)
Germany TRGS 900 Remark		AGS;DFG;EU;Y
Germany	TRGS 900 Regulatory reference	TRGS900

butane (106-97-8)		
Germany TRGS 900 Local name		Butan
Germany TRGS 900 Occupational exposure limit value (mg/m³)		2400 mg/m³
		1000 ppm
		4(II)
		DFG
		TRGS900

propane (74-98-6)		
Germany TRGS 900 Local name F		Propan
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	1800 mg/m³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Germany	TRGS 900 Limitation of exposure peaks	4(II)
Germany	TRGS 900 Remark	DFG
Germany	TRGS 900 Regulatory reference	TRGS900

HYDROCARBON WAXES (PETROLEUM), OXIDIZED (64743-00-6)
HTTDRUCARDUN WAXES (PETRULEUW), UXIDIZED (04/43-00-0)

7			/\AI_	rkers)	v
JIN	46.	/I JIVI	 LVVC	IKEIS	

Long-term - systemic effects, dermal	1,7 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0,23 mg/m³	

DNEL/DMEL (General population)

Long-term - systemic effects,oral	0,8 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0,06 mg/m ³	

Long-term - systemic effects, dermal 0,8 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater)	0,1 mg/l
PNEC aqua (marine water)	0,01 mg/l
PNEC aqua (intermittent, freshwater)	1 mg/l

PNEC (Sediment)

THE (South of the control of the con	
PNEC sediment (freshwater)	4270 mg/kg dwt
PNEC sediment (marine water)	427 mg/kg dwt

AROMATIC HYDROCARBONS, C8 (90989-38-1)

DNEL/DMEL (Workers)	EL/DMEL (Workers)	
Acute - systemic effects, inhalation	289 mg/m³	
Acute - local effects, inhalation	289 mg/m³	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m³	
Long-term - local effects, inhalation	77 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174 mg/m³	

4/10 18/12/2018 (Version: 1.0) EN (English) 18/12/2018 (Version: 1.0)

1,6 mg/kg bodyweight/day



Long-term - systemic effects,oral

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

AROMATIC HYDROCARBONS, C8 (90989-38-1)		
Long-term - systemic effects, inhalation 14,8 mg/m³		
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0,327 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater) 12,46 mg/kg dwt		

8.2. Exposure controls

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Chemical-resistant and impenetrable gloves that meet approved standards should be used whenever chemical products are handled if a risk assessment indicates that it is necessary. Nitrile gloves: Detection time> 8 hours, thickness = 0.12 mm.

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
	Polyvinylalcohol (PVA), Butyl rubber (IIR) /				EN 374

Eye protection:

Avoid contact with eyes. Splash goggles

Туре	Use	Characteristics	Standard	
Safety glasses		With side shields	EN 166	
Face shield	In the event of high danger			

Skin and body protection:

Wear suitable protective clothing. Avoid contact with the skin and the eyes. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. Wash contaminated clothes

Туре	Standard
Use chemically protective clothing, TYPE3; in the event of substantioal spatter, TYPE3; in the event of substantioal spatter	EN 14605
Use chemically protective clothing, TYPE6; In the event of a risk of splashing	EN 13034

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Aerosol mask	(FFP1), (FFP3)		EN 149
Gas mask	Gas/vapour filter		EN 14387
Dust mask	Type P1, Type P3		EN 143

Personal protective equipment symbol(s):









Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Colourless.

18/12/2018 (Version: 1.0) EN (English) 5/10 18/12/2018 (Version: 1.0)



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour : characteristic. Odour threshold : No data available : No data available pΗ Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available : ≈ -80 °C Flash point

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available

Vapour pressure at 50 °C : > 3 bar

Relative vapour density at 20 $^{\circ}$ C : No data available Relative density : No data available Density : 868 g/l @20 $^{\circ}$ C

Solubility : immiscible and insoluble.

Log Pow : No data available
Viscosity, kinematic : < 7 mm²/s @40°C
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Lower explosive limit (LEL) : 1,5 vol %

: 10 vol %

Upper explosive limit (UEL) 9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist) 2,222 mg/l/4h

acetone; propan-2-one; propanone (67-64-1)

LD50 oral rat 5800 mg/kg

ISOTRIDECANOL, ETHOXYLATED (69011-36-5)		
LD50 oral rat 300 - 2000 mg/kg		
LD50 oral	> 200 mg/kg bodyweight	
LD50 dermal rabbit	> 2000 mg/kg	
LD50 dermal > 2000 mg/kg bodyweight		

18/12/2018 (Version: 1.0) EN (English) 6/10 18/12/2018 (Version: 1.0)



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to regulation (EG) No. 1307/2000 (NEAGH) with its amendment regulation (EG) 2013/000				
HYDROCARBON WAXES (PETROLEUM), OXIDIZED (64743-00-6)				
LD50 oral rat	> 5000 mg/kg			
Skin corrosion/irritation	: Causes skin irritation.			
Serious eye damage/irritation	: Causes serious eye irritation.			
Respiratory or skin sensitisation	: Not classified			
Additional information	: Based on available data, the classification criteria are not met			
Germ cell mutagenicity	: Not classified			
Additional information	: Based on available data, the classification criteria are not met			
Carcinogenicity	: Not classified			
Additional information	: Based on available data, the classification criteria are not met			
Reproductive toxicity	: Not classified			
Additional information	: Based on available data, the classification criteria are not met			
STOT-single exposure	: May cause respiratory irritation. May cause drowsiness or dizziness.			
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure (if inhaled).			
Aspiration hazard	: Not classified.			

WYNN'S INJECTOR DECARBONIZER 500ML	
Vaporizer	Aerosol
Viscosity, kinematic	< 7 mm²/s @40°C
Potential adverse human health effects and	: Harmful if inhaled.

: Based on available data, the classification criteria are not met

symptoms

SECTION 12: Ecological information

	l. T		

Additional information

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

ISOTRIDECANOL, ETHOXYLATED (69011-36-5)		
LC50 other aquatic organisms 1	1 - 10 mg/l CYPRINUS CARPIO	
EC50 Daphnia 1	1 - 10 mg/l	
EC50 72h algae (1) 1 - 10 mg/l DESMODESMUS SUBSPICATUS		

12.2. Persistence and degradability

WYNN'S INJECTOR DECARBONIZER 500ML

Persistence and degradability Not established.

12.3. Bioaccumulative potential

WYNN'S INJECTOR DECARBONIZER 500ML

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

7/10

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

18/12/2018 (Version: 1.0) EN (English) 18/12/2018 (Version: 1.0)



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID			
14.1. UN number							
1950	1950	1950	Not regulated	Not regulated			
14.2. UN proper shippin	g name						
AEROSOLS	AEROSOLS	Aerosols, flammable	Not regulated	Not regulated			
Transport document descr	iption						
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	Not regulated	Not regulated			
14.3. Transport hazard o	class(es)						
2.1	2.1	2.1	Not regulated	Not regulated			
1 Y 2	1	№ ¥ 2	Not regulated	Not regulated			
14.4. Packing group							
Not applicable	Not applicable	Not applicable	Not regulated	Not regulated			
14.5. Environmental hazards							
Dangerous for the environment: Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Not regulated	Not regulated			
No supplementary information available							
A. 6. Special progrations for user							

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

: 190, 327, 344, 625 Special provisions (ADR)

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02 : PP87, RR6, L2 Special packing provisions (ADR)

Mixed packing provisions (ADR) : MP9 Transport category (ADR) : 2 Special provisions for carriage - Packages (ADR) : V14 Special provisions for carriage - Loading, : CV9, CV12

unloading and handling (ADR)

: S2

Special provisions for carriage - Operation (ADR) Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 : P207, LP02 Packing instructions (IMDG) Special packing provisions (IMDG) : PP87, L2 : F-D EmS-No. (Fire) EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None : SW1, SW22 Stowage and handling (IMDG) Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Y203 PCA limited quantity max net quantity (IATA) : 30kgG

18/12/2018 (Version: 1.0) EN (English) 8/10 18/12/2018 (Version: 1.0)



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

CONTRAINS THE NEACT ATTIES ATV Substances		
Allergenic fragrances > 0,01%:		
benzyl alcohol		
Detergent Regulation : Labelling of contents:		
Component	%	
aromatic hydrocarbons	>=30%	
aliphatic hydrocarbons	15-30%	
non-ionic surfactants	<5%	

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 1, Slightly hazardous to water (Classification according to

AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16

December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:			
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1		
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
Carc. 1A	Carcinogenicity, Category 1A		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1	Flammable gases, Category 1		

18/12/2018 (Version: 1.0) EN (English) 9/10 18/12/2018 (Version: 1.0)



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EO) 2015/650				
Flam. Liq. 2	Flammable liquids, Category 2			
Flam. Liq. 3	Flammable liquids, Category 3			
Muta. 1B	Germ cell mutagenicity, Category 1B			
Press. Gas	Gases under pressure			
Skin Irrit. 2	Skin corrosion/irritation, Category 2			
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2			
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis			
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation			
H220	Extremely flammable gas.			
H222	Extremely flammable aerosol.			
H225	Highly flammable liquid and vapour.			
H226	Flammable liquid and vapour.			
H229	Pressurised container: May burst if heated.			
H302	Harmful if swallowed.			
H304	May be fatal if swallowed and enters airways.			
H312	Harmful in contact with skin.			
H315	Causes skin irritation.			
H318	Causes serious eye damage.			
H319	Causes serious eye irritation.			
H332	Harmful if inhaled.			
H335	May cause respiratory irritation.			
H336	May cause drowsiness or dizziness.			
H340	May cause genetic defects.			
H350	May cause cancer.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H412	Harmful to aquatic life with long lasting effects.			
	·			

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Aerosol 1	H222;H229	On basis of test data		
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method		
Skin Irrit. 2	H315	Calculation method		
Eye Irrit. 2	H319	Calculation method		
STOT SE 3	H335	Calculation method		
STOT SE 3	H336	Calculation method		
STOT RE 2	H373	Calculation method		
Aquatic Acute 1	H400	Calculation method		
Aquatic Chronic 3	H412	Calculation method		

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

18/12/2018 (Version: 1.0)