



Digital Multimeter

9DM1361

- Date hold, auto range, auto power off selection, auto power off cancellation
- Unit & function indication, Maximum reading value 1999 digits. Negative polarity indicator (no indication is given for positive polarity)
- Low power consumption
- Fuse with : 500mA / 600V & 10A / 600V
- AAA battery x 2 PC. included
- CE approval IEC61010-1 (2010), CAT.II 600V, CAT.III 300V

Specification	
DC Voltages (0.1mV ~ 1V)	200mV / 2V / 20V / 200V / 600V
AC Voltages (0.001V ~ 1V)	2V / 20V / 200V / 600V
DC Ampere (0.1uA ~ 0.01A)	200uA / 2000uA / 20mA / 2A / 10A
AC Ampere (0.1uA ~ 0.01A)	200uA / 2000uA / 20mA / 2A / 10A
Resistance (0.1Ω ~ 0.01MΩ)	200Ω / 2kΩ / 20kΩ / 200kΩ / 2MΩ / 20MΩ
Continuity check	Yes
Diode test	Yes
hFE(NPN, PNP)	Yes
LED check	Yes
Low battery indicator	Yes
LCD Display	3 1/2 digits 2000 counts
Sampling rate	3 times / sec

KT NO.	Size (mm)		
	L x W x H		
9DM1361	138 x 70 x 32	85	10 / 60





Digital Multimeter

9DM1381

- Pocket size with flip cover design
- Approx. 4300 counts LCD display
- Auto range, auto power off selection
- Low power consumption
- LR44 battery x 2 PC. included
- CE approval EN61010-1, CAT.II 600V, CAT.III 300V
- Attachable test leads, easy operation

Specification	
DC Voltages (0.1mV ~ 1V)	400mV / 4V / 40V / 400V / 600V
AC Voltages (0.001V ~ 1V)	4V / 40V / 400V / 600V
Resistance (0.1Ω ~ 0.01MΩ)	400Ω / 4kΩ / 40kΩ / 400kΩ / 4MΩ / 40MΩ
Continuity check	Yes
Diode test	Yes
Overload indicator	OL
Low battery indicator	Yes
Sampling rate	Approx. 2 times / sec

KT NO.	Size (mm)		
	L x W x H		
9DM1381	117 x 76 x 18	121	20 / 80

