



## Technical Information

---

<b>Product name</b>	: <b>MoTip Vinyl Spray</b>	
<b>Colour</b>	: <b>White</b>	<b>Black</b>
<b>Article number</b>	: <b>04065</b>	<b>04066</b>
<b>Supplier / Producer</b>	: <b>MOTIP DUPLI B.V.</b>	
	<b>Wolfraamweg 2</b>	
	<b>NL-8471 XC WOLVEGA</b>	
	<b>Telephone number</b>	<b>+31 561 – 69 44 00</b>
	<b>Telefax number</b>	<b>+31 561 – 69 44 31</b>

---

### Product description

High quality vinyl spray to repair and embellish parts of vinyl, leather and artificial leather.

### Product characteristics

Lasting colour and lasting gloss  
Elastic  
Excellent adhesion  
Maintains the original structure

### Physical and Chemical Characteristics

Contents	: 400 ml
Base	: Nitro-cellulose binder
VOC-content	: Approximately 84% w/w
Solid content	: Approximately 16% w/w
Gloss	: Satin matt
Coverage	: 1,25 to 1,75 m <sup>2</sup>
Dust free	: After 5 to 10 minutes
Tack free	: After 10 to 20 minutes
Hardened/re-sprayable	: After 2 hours
Heat resistant	: To 50°C

### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

#### Pre Treatment

The surface should be clean, dry and free of grease.

#### Treatment

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre..

Apply the vinyl spray in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

**The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.**