MERCUSYS°

AC1200 Wireless Dual Band Router Model: AC12

Highlights

- Fast Wi-Fi Simultaneous 2.4GHz 300Mbps and 5GHz 867Mbps connection for 1.2Gbps of total available bandwidth
- 802.11ac Provides a data transfer rate 3 times faster than 802.11n for each stream
- Maximum Range Four 5dBi high gain antennas ensure widespread Wi-Fi coverage and a stable connection
- Easy Installation Intuitive webpage guides you through the setup process in minutes





MERCUSYS[®]

Applications





Ideal for average internet users seeking fast downloads, seamless streaming audio, uninterrupted streaming video, and lag-free online gaming

Features



Speed

Fast Wireless Speed - Combined wireless speeds of up to 300 Mbps (over 2.4GHz) and 867 Mbps (over 5GHz)

Range

Four Omni Directional Antennas – Four fixed antennas provide maximum wireless coverage Enhanced Signal – High gain antennas are arranged to boost wireless performance



Easy Setup

Quick 3-Step Installation - Intuitive webpage supports quick, hassle free installation



Security

Guest Network - Creates two separate networks for you and your guests to ensure safety Parental Controls – Parents can establish appropriate access policies for children devices



MERCUSYS°

Connections



Connect to desktops, C game consoles, etc. th

WAN Port: Connect to the internet



Fast Dual-Band Wi-Fi

The AC12 connects devices on both 2.4GHz and 5GHz bands simultaneously, offering a superior lag-free experience for work and play. Combining 300Mbps 2.4GHz (perfect for surfing and emailing) and 867Mbps 5GHz (ideal for HD streaming and gaming), you have the flexibility to allocate your devices to dedicated networks to do more at the same time.





Specifications

Physical Specifications

Ethernet Ports 3*10/100Mbps LAN Ports 1*10/100Mbps WAN Port

Button WPS/Reset Button

External Power Supply 9V/0.85A

Dimensions (W x D x H) 222 x 140 x 32 mm

Antenna 4 * 5dBi

Package Contents

- AC1200 Wireless Dual Band Router (AC12)
- Power Adapter
- Ethernet Cable
- Quick Installation Guide

Wireless Specifications

Wireless Standards IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz

Frequency 2412MHz ~ 2472MHz, 5150MHz ~ 5250MHz

Signal Rate 300Mbps at 2.4GHz, 867Mbps at 5GHz

Transmit Power <20dBm (EIRP)

Reception Sensitivity

5GHz • 11a 6M: -92dBm

- 11a 54M: -75dBm
- 11ac 40M MCS9: -64dBm 11n 40M MCS7: -71dBm
- 11ac 80M MCS9: -60dBm

Wireless Function

Enable/Disable Wireless Radio, Wireless Statistics

Wireless Security WPA-PSK / WPA2-PSK

Operation Specifications

WAN Type Dynamic IP/Static IP/PPPoE/L2TP/PPTP

DHCP Server

Port Forwarding Virtual Server, UPnP, DMZ

Management

Access Control Local Management Remote Management

Firewall Security IP and MAC Address Binding

Guest Network

2.4GHz Guest Network, 5GHz Guest Network

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Operating Humidity: 10%~90% Non-Condensing
- Storage Humidity: 5%~90% Non-Condensing

Specifications are subject to change without notice. MERCUSYS is a registered trademark of MERCUSYS TECHNOLOGIES CO., LTD. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2019 MERCUSYS TECHNOLOGIES CO., LTD. All rights reserved.

*Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage, and quantity of connected devices are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

www.mercusys.com



2.4GHz • 11q 6M: -95dBm

- 11g 54M: -77dBm
- 11ac 20M MCS8: -70dBm 11n 20M MCS7: -74dBm