

## ★ MINERAL ATF OIL.

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

## ★ APPLICATIONS

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

## ★ PERFORMANCE LEVEL

- ALLISON : C4
- CATERPILLAR: TO-2
- FORD: M2C-138CJ, Mercon
- GM: 6137-M DEXRON II-D
- MAN: 339 V1/Z1
- MB: 236.5
- MB: 236.7
- MB: 236.1
- VOITH: H55.6335xx
- ZF: TE-ML 03D
- ZF: TE-ML 04D
- ZF: TE-ML 09
- ZF: TE-ML 11A
- ZF: TE-ML 14A
- ZF: TE-ML 17C



## ★ FEATURES

Anti-wear protection : extended transmission life.

Extended oil life : optimized thermal and oxidation stability.

## ★ CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.867
Viscosity 40 °C	mm <sup>2</sup> /s		37.40
Viscosity 100 °C	mm <sup>2</sup> /s		7.46
Viscosity Index			171
Flash Point COC	°C		198
Pour Point	°C		-48
Total Base Number	mgKOH/g		2.4

## ★ PACKAGING

