

Technical Data Sheet



Typical Inspection Data:	
Density @ 20°C	0.842 g/cm ³
Viscosity @ 100°C	10.1 cSt
Viscosity @ 40°C	53 cSt
Viscosity Index	182
Viscosity CCS @ -35°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

Voltech 0W-30

Fully Synthetic

Official Approvals:

Approved by Volvo under 95200377 standard

Recommended by Comma for applications requiring:

ACEA A5/B5; API SL

Product Features:

- Fully synthetic, high performance 0W-30 oil, for modern Volvo petrol and diesel vehicles.
 Offers improved fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 15-11-2018

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com