



PETRONAS

TECHNICAL CHARACTERISTICS

SELENIA K P.E.

PRODUCT CODE: 1411

APPLICATION

Synthetic lubricant designed for the latest generation, low emission, petrol engines. Its specific formulation warrants the utmost protection also of high performance turbocharged engines with high thermal stress. Its low ash content helps to maintain the total cleanliness of modern catalysts.

SPECIFICATIONS

SAE 5W-40, ACEA C3, API SN/CF,
FIAT 9.55535-S2 CONTRACTUAL TECHNICAL REFERENCE N°F603.C07, MB-Approval 229.51,
VW 502.00-505.00, VW 505.01, BMW LL-04

TEST DESCRIPTION

| TEST DESCRIPTION | METHOD | UNIT | TYPICAL VALUE |
|-----------------------|------------|-------------------|---------------|
| APPEARANCE | -- | -- | B. & C. |
| DENSITY AT 15°C | ASTM D4052 | g/cm ³ | 0,850 |
| VISCOSITY AT 100°C | ASTM D445 | cSt | 14 |
| VISCOSITY INDEX | ASTM D2270 | -- | 175 |
| FLASH POINT CI. O. C. | ASTM D92 | °C | > 200 |
| T.B.N. | ASTM D2896 | mg KOH/g | > 7 |
| POUR POINT | ASTM D97 | °C | <-33 |

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

08/2016