



DYNAMIC 420 START 230V 12-24V



Обзор

DYNAMIC 420 START 230V 12-24V

cod. 829382

Battery charger and starter for charging free electrolyte batteries (WET) with 12/24V voltage and starting all kinds of cars, vans and light trucks.

Features:

- choice of normal charge, quick charge (BOOST), quick start
- display of charging and starting current
- protection against overloads and polarity reversal.



1 PH 230В



МАРКИРОВКА CE



СЕРТИФИКАЦИИ EAC

Технические данные

CODE	КОД 829382	A_{EFF}	ТОК ЭФФЕКТИВНОГО ЗАРЯДА 75 А		РЕГУЛИРОВКА ПОЗИЦИИ 4
V_{1PH}	ОДНОФАЗНОЕ НАПРЯЖЕНИЕ СЕТИ 230 V	A_{EN}	ТОК КОНВЕНЦИОНАЛЬНОГО ЗАРЯДА EN60335-2-29 50 А		РАЗМЕРЫ 30,5 x 36 x 63 cm
F	ЧАСТОТЫ СЕТИ 50 / 60 Hz	A_{1V/C}	ТОК ЗАПУСКА 1V / C EN60335-2-29 300 А		ВЕС 16,4 kg
P_{CHARGE}	МОЩНОСТЬ ЗАРЯДА 1,6 kW	A_{START MAX}	МАКСИМАЛЬНЫЙ ТОК ПУСКА 400 А		КОД EAN 800489773284 8
P_{START}	МОЩНОСТЬ ЗАПУСКА 10 kW	C_{MIN}	МИН. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 20 А		ЧАСТЕЙ / ПАЛЛЕТ 18 pz/pallet
	НАПРЯЖЕНИЕ ЗАРЯДКИ 12 / 24 V	C_{MAX}	МАКС. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 1000 А		

Входящие в комплект аксессуары

Telwin SPA | Via della Tecnica 3 - 36030 VILLAVERLA (VI) ITALY - Tel. +39-0445-858811 - Fax +39-0445-858800/801 - www.telwin.com
01.09.2020



DYNAMIC 420 START 230V 12-24V



null - 712001



null - 712002