



T-CHARGE 12 6V/12V



NEW

Обзор

T-CHARGE 12 6V/12V

cod. 807567

Multifunction, battery charger and maintainer for 6/12V WET, GEL, AGM, MF, PbCa, EFB batteries.

Choice of 3 charge voltages in Pulse Tronic: 6V, 12V/1A (motos), 12V/4A (autos).

Advanced specific functions for the charge and maintenance of batteries at low temperatures and of AGM batteries.

The activation of the RECOVERY function allows for the recovery of sulphated batteries.

Features:

- Automatic charge and maintenance in Pulse Tronic;
- 3 charge voltages;
- Led visualization of the charge level;
- AGM function for the charge and maintenance of AGM batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- Protections against overloads, shortcircuit and polarity reversal.

Equipped with cable with clamps and cable with eyelets.



1 PH 230V



МАРКИРОВКА CE



СЕРТИФИКАЦИИ EAC

Технические данные

CODE	КОД 807567	ТОК КОНВЕНЦИОНАЛЬНОГО ЗАРЯДА EN60335-2-29 1 / 4 A	РАЗМЕРЫ 17 x 6,5 x 3,5 cm
V _{IPH}	ОДНОФАЗНОЕ НАПРЯЖЕНИЕ СЕТИ 230 V	МИН. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 2 A	ВЕС 0,6 kg
F	ЧАСТОТЫ СЕТИ 50 / 60 Hz	МАКС. НОМИНАЛЬНАЯ ССЫЛКА ПОТЕНЦИАЛ 70 A	КОД EAN 800489798045 4
P	ПОГЛОЩЕННАЯ МОЩНОСТЬ ЗАРЯДА 55 W	РЕГУЛИРОВКА ПОЗИЦИИ 2	ЧАСТЕЙ / ПАЛЛЕТ 432 pz/pallet



T-CHARGE 12 6V/12V



НАПРЯЖЕНИЕ ЗАРЯДКИ 6 / 12 V



СТЕПЕНЬ ЗАЩИТЫ IP65



ЧАСТЕЙ / ПАЛЛЕТ - В 288 pz/pallet-B



ТОК ЭФФЕКТИВНОГО ЗАРЯДА 1 / 4 А