




### GV Etna 4.1



Watch the video on youtube:  
[www.youtube.com/lavorpro](http://www.youtube.com/lavorpro)



#### Equipped with:

- Stainless steel body AISI 304
- Ready steam warning lamp
- Boiler 3 kW S.S. AISI 304 - Thickness 25/10
- Low level water lamp indicator
- Boiler is refilled continuously
- Switch for using chemicals and detergents mixed with steam
- Device for cleaning hot water mixed with steam
- Washable filter
- Flex hose 4 m
- Recovery tank capacity 64 l
- Drain hose system
- Steam regulation
- Wheels suitable for use in food processing area
- ON/OFF main switch with indicator lamp
- ON/OFF boiler switch with indicator lamp
- Boiler capacity 4 litres.
- Suction speed Control (Only code 8.451.0201)

#### Standard equipment:

- 5.211.0123 Hose 4 m (mod. GV Etna 4.1)
- 5.211.0124 Hose 4 m (mod. GV Etna 4.1 FR)



- 3.753.0141



- 3.754.0278



- 3.754.0005



- 3.754.0192



- 3.754.0109



- 3.754.0108



- 3.754.0110



- 6.405.0245



- 3.754.0194



- 3.754.0215



- 3.754.0196



- 3.754.0197



- 3.754.0204




- 3.754.0260



- 3.754.0271



- 5.212.0178



- 4.408.0454 - Sponge accessory

|  | GV Etna 4.1               | GV Etna 4.1 FR            |
|--|---------------------------|---------------------------|
| Code   | 8.451.0201                | 8.451.0210                |
| Max steam pressure/temperature/ Steam production | 7 bar/165° C/3,25 kg/h    | 7 bar/165° C/3,25 kg/h    |
| Boiler absorbed power                            | 3000 W/230V ~ 50Hz (Ph 1) | 3000 W/230V ~ 50Hz (Ph 1) |
| Vacuum motor absorbed power                      | 1200 W                    | 1200 W                    |
| Column depression/Air flow                       | 20.39 kPa/220 m³/h        | 20.39 kPa/220 m³/h        |
| Water tank/detergent tank capacity               | 5 l/5 l                   | 5 l/5 l                   |



New simple and intuitive control panel, quick-coupling steam gun, main ON/OFF switch with lamp, boiler ON/OFF switch with lamp, steam/detergent regulator/selector, steam flow rate regulator, steam ready warning lamp, low level water indicator lamp with buzzer, steam pressure gauge. Gun with integrated start-up control, adjustment of the vacuum power and steam function activation key.

Unlimited autonomy thanks to the continuous power supply of the boiler, which enables water top-ups in the tank without having to stop the machine or interrupt work. Discharge pipe to quickly drain dirty water collected without removing the head. Two-stage bypass vacuum motor with cyclone effect.



Equipped with 3 pumps: boiler, detergent and water. Maximum safety thanks to the 2 safety thermostats, 1 pressure switch and 1 mechanical maximum pressure valve.

## Fields of applications

**Steam system:** Food & beverage (food industry, catering, beverage, winery).

Hospitality, community & healthcare (hospitality, buildings cleaning, spa & sport, education & community, healthcare).

Industry (industry, transportation, car washers, car dealers).

