

---

<b>Product name</b>	:	<b>MoTip Tar Spray</b>
<b>Article number</b>	:	<b>090308</b>
<b>Supplier / Producer</b>	:	<b>MOTIP DUPLI B.V.</b> <b>Wolframweg 2</b> <b>NL-8471 XC WOLVEGA</b> <b>Telephone number</b> +31 561 – 69 44 00 <b>Telefax number</b> +31 561 – 69 44 31

---

### Product description

High quality lubricant and preservative on basis of Stockholm tar to prevent wear and sticking of screwed connections which are liable to heavy workload.

### Applications

Agricultural machinery  
Industrial machinery  
Truck  
Off the road vehicle

### Product characteristics

Lasting protection  
Water-repellent  
Excellent adhesion  
Prevents wear and sticking  
Resistant to weather influences  
Resistant to weak acids and bases  
Excellent corrosion prevention  
Directed jetspray  
360° Valve

### Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Stockholm Tar
VOC-content	:	Approximately 75% w/w
Colour	:	Transparent brown
Scent	:	Characteristic
Relative density at 20°C	:	0,76 g/ml
Yield	:	1 – 1,5 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
Temperature resistant	:	-30°C tot +180°C



### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C.  
Before use, shake the aerosol.

Spray parts to be treated prior to assembly. After evaporation a protective film remains, which simplifies the future disassembly. The protective film can be removed with MoTip Industrial Cleaner.