

## MOTIP PTFE Dry

Ord.-no.: 090201, 290201

## Technical Information



Loosen jammed parts with MOTIP PTFE Dry and make sure the windscreen wipers, safety belts, door locks, hinges, etc. run smoothly again. PTFE Dry is dry surface lubricant that removes oil and grease from metal and plastic parts. It has a very low friction factor preventing wear and sticking, offers excellent adhesion and is resistant to the weather. Suitable for parts that are subjected to light loads and low speed. It can be used as a release agent for moulds when the use of silicone is not required.

### Quality & properties

- No residues of oil or grease (dry film)
- Very low friction factor
- Prevents wear and sticking
- Suitable for parts which are liable to light load and low speed
- Suitable as release agent for moulds, where the use of silicones is not desired
- Excellent adhesion
- Resistant to weather influences
- Directed jetspray

### Physical & chemical data

- Base: PTFE
- Colourname:
  - ◊ Transparent white
  - ◊ transparent white
- Surfaces: Rails, Folding Roofs, Door locks, Safety belts, Zippers, Wipers, Towing hooks, Seat rails, Oven hinges, Window rails
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,74
- Vapour pressure: 3500/20 bar
- Flash point: n.a.
- Relative density: 1.74 g/ml
- Storage stability: 10 years
- Content:
  - ◊ 500 ML
  - ◊ 200 ml

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply PTFE dry in a thin layer. After evaporation of the solvent (approximately 1 minute) a protecting, dry PTFE film will remain.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.

