

DHI-LM32-P301A 31.5" QHD Monitor



Features:

• The 2560*1440 resolution produces clearer and more vivid pictures;

· IPS panel for wide viewing angles with 3-sided frameless design;

· 178°H/178°V extra-wide viewing angle for overall viewing performance;

• The 10bit(1.70B colors) panel has 99% sRGB, 100% NTSC, 95% DCI-P3, 92% Adobe RGB color gamut. It meets the designer's pursuit of image texture;

• Rich interfaces, 65W type-C can support reverse charging;

 \cdot 4ms fast response time with no image blurring or ghosting.

· Supporting PIP/PBP to display the screens of two devices on the display simultaneously.

 \cdot The angle can be adjusted to meet different needs.

Technical Specification

Model					
Model	DHI-LM32-P301A	Power Type	Adapter		
Display		Consumption (Standard)	Typ. 52W, Max. 145W		
Screen Size	31.5"	Consumption (Standby)	≤0.5W		
Panel type	IPS	Net Weight	7.7kg		
Aspect Ratio	16:9	Gross Weight	10.69kg		
Resolution	2560x1440	Tilt Angles	-5° ±2° ~15° ±2°		
Backlight	E-LED	Swivel(angle)	15°		
Brightness/Luminance	350nits(typ)	Pivot(angle/direction)	0°~180°		
Contrast Ratio	1200:1	Height Adjustment	100+/-5mm		
Color Support	99% sRGB, 100% NTSC, 95% DCI-P3, 92% Adobe RGB	VESA	75x75mm		
Viewing Angle(H/V)	178°(H)/178°(V)	Dimension(W×H×D)	718.59*422.07*45.10mm(without stand)		
Response time	4ms (OD)	Package(W×H×D)	821x183x530mm		
Refresh Rate	75Hz	Work Environment	Temperature	0°~40°(32°F~104°F)	
Signals		work Environment	Humidity	10%~85%	
Interface	DP1.4×1, HDMI 2.1×1, Type C 65W×1, Audio out×1	Accessory			
General		Standard	HDMI 1.5m Cable, Power cable, Adapter,Stand,Base		
Power Supply	DC 19V 7.89A		· · · · · · · · · · · · · · · · · · ·		

Rev 002.000

© 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product



www.dahuasecurity.com