

SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

Revision date: 19.07.2018

1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product details

Trade name: Fiberglass Putty

Article number: 15032, 15034, 15035, 15036, 15039

Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Sector of Use:

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Intended use: Car refinishing Product/Knife filler/ Surfacer

Manufacturer/Supplier: Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

Further information obtainable from: Product Safety Department

Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.

Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P281 Use personal protective equipment as required.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents / container in accordance with regional regulations.

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS**Chemical characterization: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	25-<50%
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32-xxxx	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	12.5-<20%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.
For the wording of the listed hazard phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

Most important symptoms and effects, both acute and delayed: No further relevant information available.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available

5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Advice for firefighters -

Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 3

Specific end use(s) No further relevant information available.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
7727-43-7 barium sulphate, natural	
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
100-42-5 styrene	
WEL	Short-term value: 1080 mg/m ³ , 250 ppm Long-term value: 430 mg/m ³ , 100 ppm

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Avoid contact with the eyes.

Respiratory protection:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.KCL Camatril, article no. 898 or similar products.

Solvent resistant gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Natural rubber, NR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Natural rubber, NR

Eye protection: Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	<i>Pasty</i>
Colour:	<i>According to product specification</i>
Odour:	<i>Characteristic</i>
Odour threshold:	<i>Not determined.</i>
pH-value:	<i>Not determined.</i>
Change in condition	
Melting point/freezing point:	<i>Undetermined.</i>
Initial boiling point and boiling range:	<i>145 °C (293 °F)</i>
Flash point:	<i>31 °C (87.8 °F)</i>
Flammability (solid, gas):	<i>Not applicable.</i>
Ignition temperature:	<i>480 °C (896 °F)</i>
Decomposition temperature:	<i>Not determined.</i>
Explosive properties:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
Explosion limits:	
Lower:	<i>1.2 Vol %</i>
Upper:	<i>8.9 Vol %</i>
Vapour pressure at 20 °C (68 °F):	<i>6 hPa (4.5 mm Hg)</i>
Density at 20 °C (68 °F):	<i>1.95 g/cm³ (16.27 lbs/gal)</i>
Relative density	<i>Not determined.</i>
Vapour density	<i>Not determined.</i>
Evaporation rate	<i>Not determined.</i>
Solubility in / Miscibility with water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient: n-octanol/water:	<i>Not determined.</i>

Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
Solvent content:	
Organic solvents:	13.4 %
VOC- (EC)	---
	227.0 g/l
VOC-EU%	11.64 %
Solids content:	87.3 %
Other information	<i>No further relevant information available.</i>

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11- TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13– DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 04	metallic packaging

Uncleaned packaging:

Recommendation: Non contaminated packagings may be recycled.

14– TRANSPORT INFORMATION

UN-Number

ADR, IMDG, IATA UN3269

UN proper shipping name

ADR 3269 POLYESTER RESIN KIT
IMDG, IATA POLYESTER RESIN KIT

Transport hazard class(es)

ADR



Class 3 (FT3) Flammable liquids.
Label 3

IMDG, IATA



Class 3 Flammable liquids.
Label 3

Packing group

ADR, IMDG, IATA III

Environmental hazards: Not applicable.

Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): -

EMS Number: F-E,S-D

Stowage Category A

**Transport in bulk according to Annex II of
Marpol and the IBC Code** Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: See

Transport category 3

Tunnel restriction code E

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: See SP340

UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or
Chamaleon GmbH- Safety Data Sheet

mixture .

Directive 2012/18/EU

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57
--

None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16-OTHER INFORMATION

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.