

Product Highlights

Flexibility and Reliability

A combination of RJ-45, SFP, and Combo ports provides the necessary flexibility to adapt to a wide range of applications and environments

Flexible Management

A multilingual Web UI, full command CLI, SNMP, and a variety of management features allow the switches to integrate with your existing network

Power over Ethernet

Increased PoE capability and support for IEEE 802.3af/at allow the PoE models in the series to power more devices with greater port density



DGS-1210 Series

Metro Ethernet Switches

Features

Flexible Hardware Design

- Available in multiple configurations:
 - Different combinations of 1000BASE-T, 100/1000 GbE/SFP combo, and 10/1000 SFP
 - PoE and non-PoE variations
- Designed for standard 1U rack-mounting

Layer 2 Features

- 8K or 16K MAC address table
- IEEE 802.1D STP, 802.1w RSTP, and 802.1s MSTP
- Loopback detection
- Supports IEEE 802.3ad Link Aggregation
- Port-based Q-in-Q

Security and Authentication

- Access Control Lists (ACLs)
- IP-MAC-Port Binding (IMPB)
- D-Link Safeguard Engine helps the CPU resist broadcast/multicast/unicast flooding
- Port Security

Intuitive Management

- D-Link Network Assistant (DNA) utility or multilingual Web UI
- Command Line Interface (CLI) through Telnet or SSH

The DGS-1210 Series Metro Ethernet Switches are a range of switches designed to provide increased Power over Ethernet (PoE) output, a range of physical interface types, multiple management interfaces, and advanced Layer 2 features. With all of these features combined, the DGS-1210 Series provides a cost-efficient and flexible solution for expanding any business network.

Seamless Integration

The DGS-1210 Series includes a wide range of port and media types, including 10/100/1000BASE-T RJ-45 ports, 100/1000 Mbps GbE/SFP combo ports, and 100/1000 Mbps SFP ports. The DGS-1210-10, DGS-1210-26, DGS-1210-10P and DGS-1210-10MP models feature 2 100/1000 Mbps SFP ports, while all other DGS-1210 Series models feature 2 or 4 GbE/SFP combo ports, allowing you to choose the most suitable media type for your requirements. All DGS-1210 Series PoE switches include support for IEEE 802.3af/at and higher power budgets, allowing more PoE devices to be powered by the switch and for devices to be installed in remote locations without immediate access to power outlets.

Advanced Features

The DGS-1210 Series comes equipped with a complete lineup of L2 features, including IGMP snooping, port mirroring, Spanning Tree Protocol (STP), and Link Aggregation Control Protocol (LACP). The IEEE 802.3x Flow Control function allows servers to directly connect to the switch for fast, reliable data transfers. Network maintenance features include loopback detection and cable diagnostics. Loopback detection significantly speeds up troubleshooting by automatically detecting and shutting down switching loops. The cable diagnostics feature, designed primarily for administrators and customer service representatives, determines the cable quality and quickly discovers errors, allowing for hassle-free diagnostics and maintenance.

Efficient and Resilient Networking

The DGS-1210 Series supports up to 6 kV surge protection on all Ethernet ports, protecting the switch from the damage caused by power surges due to lightning strikes or faulty electrical cabling. The switches also support 802.3ad Link Aggregation, which allows grouping of multiple ports to provide redundancy and load balancing in mission-critical environments. Combined, the two features ensure the reliability of data transmission in your network.

Security & Authentication

The DGS-1210 Series supports Auto Voice VLAN and Auto Surveillance VLAN Mode, which allows voice and video traffic to be automatically identified and handled differently than regular network traffic. Auto Voice VLAN detects Voice over IP (VoIP) traffic and automatically segments it from the rest of the network, adding a layer of isolation and allowing Quality of Service (QoS) to be applied. Surveillance Mode detects compatible ONVIF cameras and places them in a surveillance VLAN, allowing a single switch to be used for voice, video, and data, removing the need for dedicated hardware and reducing maintenance costs. Surveillance Mode also includes its own Web UI, making surveillance features easily accessible and simplifying management of your surveillance network.

Advanced Access Control

D-Link's innovative Safeguard Engine helps to protect the switches against traffic flooding caused by malicious attacks. DGS-1210 Series supports 802.1X port-based authentication, allowing the clients to be authenticated through external RADIUS servers. The Access Control List (ACL) feature helps to enhance network security and helps to protect the internal IT network. To help prevent ARP spoofing attacks, the switch uses packet control ACLs to block invalid packets that contain fake ARP messages.

Versatile Management

The DGS-1210 Series comes with the D-Link Network Assistant (DNA) utility that enables administrators to remotely control their network down to the port level. The D-Link Network Assistant utility furthermore allows customers to easily discover multiple D-Link Smart Managed Switches within the same L2 network segment and display them on-screen for instant access. With this utility, users do not need to change the IP address of their PC. This allows for simultaneous configuration and setup of all discovered devices, including password changes and firmware upgrades. The DGS-1210 Series also supports Command Line Interface (CLI) through Telnet or SSH.

Technical Specifications			
Model Number	DGS-1210-10	DGS-1210-10P	DGS-1210-10MP
Hardware Version	R1	R1	R1
Interface			
Size	<ul style="list-style-type: none"> • 11-inch standard rack-mount width • 1U height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U height 	<ul style="list-style-type: none"> • 19-inch standard rack-mount width • 1U height
Interfaces	<ul style="list-style-type: none"> • 8 x 10/100/1000BASE-T ports • 2 x 100/1000 Mbps SFP ports 	<ul style="list-style-type: none"> • 8 x 10/100/1000BASE-T PoE ports • 2 x 100/1000 Mbps SFP ports 	<ul style="list-style-type: none"> • 8 x 10/100/1000BASE-T PoE ports • 2 x 100/1000 Mbps SFP ports
Port Standards & Functions	<ul style="list-style-type: none"> • Ports 1 to 8 compliant with IEEE 802.3ab 	<ul style="list-style-type: none"> • Ports 1 to 8 compliant with IEEE 802.3at 	<ul style="list-style-type: none"> • Ports 1 to 8 compliant with IEEE 802.3at
Other Port Standards & Functions	<ul style="list-style-type: none"> • IEEE 802.3i 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper) <ul style="list-style-type: none"> • Auto-negotiation • IEEE 802.3x Flow Control • IEEE 802.3z 1000BASE-X Gigabit Fiber 		
Network Cables	<ul style="list-style-type: none"> • UTP Cat. 5, Cat. 5e (100 m max.) 		
Full/Half-Duplex	<ul style="list-style-type: none"> • Full/half-duplex for 10/100 Mbps speeds • Full-duplex for 1000 Mbps speed 		
Media Interface Exchange	<ul style="list-style-type: none"> • Auto MDI/MDIX adjustment for all twisted-pair ports 		
Performance			
Switching Capacity	<ul style="list-style-type: none"> • 20 Gbps 		
Forwarding Method	<ul style="list-style-type: none"> • Store-and-forward 		
MAC Address Table Size	<ul style="list-style-type: none"> • 8K entries 		
MAC Address Update	<ul style="list-style-type: none"> • Up to 256 static MAC entries 		
64-byte Max. Forwarding Rate	<ul style="list-style-type: none"> • 14.88 Mpps 		
CPU Memory	<ul style="list-style-type: none"> • 256 MB DDR3 		
Packet Buffer	<ul style="list-style-type: none"> • 4.1 Mbits 		
Flash Memory	<ul style="list-style-type: none"> • 32 MB 		
LEDs			
Power (per device)	✓	✓	✓
Link/Active/Speed (per port)	✓	✓	✓
Physical/Environmental			
MTBF	<ul style="list-style-type: none"> • 1,380,058 hours 	<ul style="list-style-type: none"> • 729,258 hours 	<ul style="list-style-type: none"> • 1,274,005 hours
Acoustic	<ul style="list-style-type: none"> • 0 dB(A) 	<ul style="list-style-type: none"> • 0 dB(A) 	<ul style="list-style-type: none"> • 0 dB(A)
Heat Dissipation	<ul style="list-style-type: none"> • 21.59 BTU/hr 	<ul style="list-style-type: none"> • 279.59 BTU/hr 	<ul style="list-style-type: none"> • 519.51 BTU/hr
Power Input	<ul style="list-style-type: none"> • AC Input: 100 to 240 V AC, 50/60 Hz internal universal power supply 	<ul style="list-style-type: none"> • AC Input: 54.0V DC external power supply 	<ul style="list-style-type: none"> • AC Input: 100 to 240 V AC, 50/60 Hz internal universal power supply
Maximum Power Consumption	<ul style="list-style-type: none"> • 6.33 W 	<ul style="list-style-type: none"> • 81.9 W (PoE on) • 7.6 W (PoE off) 	<ul style="list-style-type: none"> • 152.3 W (PoE on) • 9.4 W (PoE off)

Maximum PoE Budget	• N/A	• 65 W	• 130 W
Standby Power Consumption	• 2.03 W/100 V • 2.07 W/240 V	• 2.5 W/100 V • 2.5 W/240 V	• 4.3 W/100 V • 5.2 W/240 V
Dimensions (W x D x H)	• 280 x 126 x 44 mm	• 280 x 126 x 44 mm	• 330 x 180 x 44 mm
Ventilation	• Fanless	• Fanless	• Fanless
Weight	• 0.98 kg	• 0.95 kg	• 1.77 kg
Power Surge Protection	• 6KV surge protection		
Operating Temperature	• -5 to 50 °C (23 to 122 °F)		
Storage Temperature	• -40 to 70 °C (-40 to 158 °F)		
Operating Humidity	• 10% to 90% non-condensing		
Storage Humidity	• 5% to 90% non-condensing		
EMI	• FCC class A, CE class A, IC, VCCI, BSMI		
Safety Certifications	• cUL, UL, CB, BSMI		

Technical Specifications

Model Number	DGS-1210-20	DGS-1210-26	DGS-1210-28
Hardware Version	R1	R1	R1
Interface			
Size	• 19-inch standard rack-mount width • 1U height	• 19-inch standard rack-mount width • 1U height	• 19-inch standard rack-mount width • 1U height
Interfaces	• 16 x 10/100/1000BASE-T ports • 4 x 100/1000 Mbps GbE/SFP combo ports	• 24 x 10/100/1000BASE-T ports • 2 x 100/1000 Mbps GbE/SFP ports	• 24 x 10/100/1000BASE-T ports • 4 x 100/1000 Mbps GbE/SFP combo ports
Port Standards & Functions	• Ports 1 to 16 compliant with IEEE 802.3ab	• Ports 1 to 24 compliant with IEEE 802.3ab	• Ports 1 to 24 compliant with IEEE 802.3ab
Console Port	• N/A		
Other Port Standards & Functions	<ul style="list-style-type: none"> • IEEE 802.3i 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper) <ul style="list-style-type: none"> • Auto-negotiation • IEEE 802.3x Flow Control • IEEE 802.3z 1000BASE-X Gigabit Fiber 		
Network Cables	• UTP Cat. 5, Cat. 5e (100 m max.)		
Full/Half-Duplex	<ul style="list-style-type: none"> • Full/half-duplex for 10/100 Mbps speeds • Full-duplex for 1000 Mbps speed 		
Media Interface Exchange	• Auto MDI/MDIX adjustment for all twisted-pair ports		

Performance			
Switching Capacity	• 40 Gbps	• 52 Gbps	• 56 Gbps
Forwarding Method	• Store-and-forward		
MAC Address Table Size	• 8K entries		
MAC Address Update	• Up to 256 static MAC entries		
64-byte Max. Forwarding Rate	• 77.4 Mpps		
CPU Memory	• 256 MB DDR3		
Packet Buffer	• 4.1 MBits		
Flash Memory	• 32 MB		
LEDs			
Power (per device)	✓	✓	✓
Link/Active/Speed (per port)	✓	✓	✓
Physical/Environmental			
MTBF	• 100,087,100 hours	• 1,082,534 hours	• 992,594 hours
Acoustic	• High speed: 47.3 dB(A) • Low speed: 37.8 dB(A)	• High speed: 50.1 dB(A) • Low speed: 40.4 dB(A)	• High Speed: 55.2 dB(A) • Low Speed: 49.3 dB(A)
Heat Dissipation	• 44.62 TU/hr	• 51.93 TU/hr	• 59.09 TU/hr
Power Input	• AC Input: 100 to 240 V AC, 50/60 Hz interal universal power supply		
Maximum Power Consumption	• 13.08 W	• 15.22 W	• 17.32 W
Standby Power Consumption	• 5.47 W/100 V • 5.56 W/240 V	• 5.01 W/100 V • 5.06 W/240 V	• 6.49 W/100 V • 6.55 W/240 V
Dimensions (W x D x H)	• 280 x 180 x 44 mm	• 440 x 140 x 44 mm	• 440 x 140 x 44 mm
Ventilation	• Fanless		
Weight	• 1.75 kg	• 2.06 kg	• 2.15 kg
Power Surge Protection	• 6KV surge protection		
Operating Temperature	• -5 to 50 °C (23 to 122 °F)		
Storage Temperature	• -40 to 70 °C (-40 to 158 °F)		
Operating Humidity	• 10% to 90% non-condensing		
Storage Humidity	• 5% to 90% non-condensing		
EMI	• FCC class A, CE class A, IC, VCCI, BSMI		
Safety Certifications	• cUL, UL, CB, BSMI		

Technical Specifications				
Model Number	DGS-1210-28P	DGS-1210-28MP	DGS-1210-52	DGS-1210-52MP
Hardware Version	R1	R1	R1	R1
Interface				
Size	• 19-inch standard rack-mount width • 1U height	• 19-inch standard rack-mount width • 1U height	• 19-inch standard rack-mount width • 1U height	• 19-inch standard rack-mount width • 1U height
Interfaces	• 24 x 10/100/1000BASE-T PoE ports • 4 x 100/1000 Mbps GbE/SFP combo ports	• 24 x 10/100/1000BASE-T PoE ports • 4 x 100/1000 Mbps GbE/SFP combo ports	• 48 x 10/100/1000BASE-T ports • 4 x 100/1000 Mbps GbE/SFP combo ports	• 48 x 10/100/1000BASE-T PoE ports • 4 x 100/1000 Mbps GbE/SFP combo ports
Other Port Standards & Functions	<ul style="list-style-type: none"> • IEEE 802.3i 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper) <ul style="list-style-type: none"> • Auto-negotiation • IEEE 802.3x Flow Control • IEEE 802.3z 1000BASE-X Gigabit Fiber 			
Network Cables	• UTP Cat. 5, Cat. 5e (100 m max.)			
Full/Half-Duplex	<ul style="list-style-type: none"> • Full/half-duplex for 10/100 Mbps speeds • Full-duplex for 1000 Mbps speed 			
Media Interface Exchange	• Auto MDI/MDIX adjustment for all twisted-pair ports			
Performance				
Switching Capacity	• 56 Gbps	• 56 Gbps	• 104 Gbps	• 104 Gbps
64-byte Max. Forwarding Rate	• 41.7 Mpps	• 41.7 Mpps	• 77.4 Mpps	• 77.4 Mpps
MAC Address Table Size	• 8K entries		• 16K entries	
CPU Memory	• 256 MB DDR3			
Packet Buffer	• 4.1 MBits	• 4.1 MBits	• 12 MBits	• 12 MBits
Flash Memory	• 32 MB			
LEDs				
Power (per device)	✓	✓	✓	✓
Link/Active/Speed (per port)	✓	✓	✓	✓
Physical/Environmental				
MTBF	• 469,262 hours	• 277,967 hours	• 400,667 hours	• 236,667 hours
Acoustic	• High speed: 51.7 dB(A) • Low speed: 44.9 dB(A)	• High speed: 51.7 dB(A) • Low speed: 44.9 dB(A)	• 0 dB(A)	• High speed: 52.4 dB(A) • Low speed: 47.6 dB(A)
Heat Dissipation	• 900.36 TU/hr	• 1521.99 TU/hr	• 118.92 TU/hr	• 1634.01 TU/hr
Power Input	• AC Input: 100 to 240 V AC, 50/60 Hz internal universal power supply			
Maximum Power Consumption	• 236.9 W/100 V (PoE on) 30.6 W/240 V (PoE off)	• 446.1 W/100 V (PoE on) 29.8 W/240 V (PoE off)	• 34.85 W	• 478.9 W/100 V (PoE on) 54.4 W/240 V (PoE off)
Standby Power Consumption	• 19.6 W/100 V • 16.6 W/240 V	• 18.5 W/100 V • 17.1 W/240 V	• 13.7 W/100 V • 13.9 W/240 V	• 32 W/100 V • 31.6 W/240 V

Dimensions (W x D x H)	• 440 x 250 x 44 mm	• 440 x 250 x 44 mm	• 440 x 210 x 44 mm	• 440 x 430 x 44 mm
Ventilation	• 2 x Smart fan	• 2 x Smart fan	• Fanless	• 3 x Smart fan
Weight	• 3.75 kg	• 3.94 kg	• 3.46 kg	6.26 kg
Power Surge Protection	• 6KV surge protection			
Operating Temperature	• -5 to 50 °C (23 to 122 °F)			
Storage Temperature	• -40 to 70 °C (-40 to 158 °F)			
Operating Humidity	• 10% to 90% non-condensing			
Storage Humidity	• 5% to 90% non-condensing			
EMI	• FCC class A, CE class A, VCCI, BSMI			
Safety Certifications	• CE, LVD, UL, CB			

Software

L2 Features	<ul style="list-style-type: none"> • MAC address table: 8K or 16K entries • Spanning Tree Protocols <ul style="list-style-type: none"> - 802.1D STP - 802.1w RSTP - 802.1s MSTP • Loopback detection 	<ul style="list-style-type: none"> • Mirroring <ul style="list-style-type: none"> - Support 1 mirroring group - Support One-to-One, Many-to-One, - Support mirroring based on Tx and Rx • Link aggregation <ul style="list-style-type: none"> - Compliant with 802.3ad - Supports max. 4 groups, 8 ports per group
L2 Multicasting	<ul style="list-style-type: none"> • IGMP Snooping <ul style="list-style-type: none"> - IGMP v1/v2/v3 snooping, v3 awareness - IGMP authentication/filtering - Supports 256 groups - VLAN/host-based IGMP snooping fast leave 	<ul style="list-style-type: none"> • MLD Snooping <ul style="list-style-type: none"> - MLD v1, MLD v2 - Supports 256 groups
VLAN	<ul style="list-style-type: none"> • 802.1Q tagged VLAN • VLAN group • Max. 256 VLAN groups • Port-based VLAN • Asymmetric VLAN • Max. 256 dynamic VLAN 	<ul style="list-style-type: none"> • Port-based Q-in-Q • ISM VLAN (multicast VLAN) • Voice VLAN • Auto surveillance VLAN • Selective QinQ • VLAN Translation
L3 Features	<ul style="list-style-type: none"> • Max. 128 ARP entries • Supports 128 static ARP entries 	<ul style="list-style-type: none"> • Default route • 1 IP interfaces • IPv6 Neighbor Discovery (ND)
Quality of Service (QoS)	<ul style="list-style-type: none"> • CoS based on: <ul style="list-style-type: none"> - Switch port - DSCP • Bandwidth control <ul style="list-style-type: none"> - Port-based (ingress, min. granularity 16 Kbps) 	<ul style="list-style-type: none"> • Queue handling <ul style="list-style-type: none"> - Strict priority (SPQ) - Weighted Round Robin (WRR) • 8 outbound queues
Access Control List (ACL)	<ul style="list-style-type: none"> • ACL based on <ul style="list-style-type: none"> - MAC address - TOS - IPv4/v6 address - DSCP - TCP/UDP port - Protocol 	<ul style="list-style-type: none"> • Up to 200 ingress access rules • Up to 150 ingress access profiles • ACL action (permit/deny)

Authentication, Authorization, and Accounting (AAA)	<ul style="list-style-type: none"> • 802.1X <ul style="list-style-type: none"> - Host-based access control - Port-based access control • Guest VLAN • RADIUS accounting 	<ul style="list-style-type: none"> • User account privilege (4 level user access) • Authentication for management access <ul style="list-style-type: none"> - Local, RADIUS
Security	<ul style="list-style-type: none"> • Port security (Up to 64 MAC addresses per port) • Smart IP-MAC-Port Binding (Smart IMPB) <ul style="list-style-type: none"> • ARP Inspection <ul style="list-style-type: none"> • Max. 256 entries • IPv4 Inspection <ul style="list-style-type: none"> • Max. 127 entries • IPv6 Inspection <ul style="list-style-type: none"> • Max. 63 entries • DHCP Snooping <ul style="list-style-type: none"> • Max. 512 entries 	<ul style="list-style-type: none"> • Broadcast/Multicast/Unicast storm control • IP Source Guard • D-Link Safeguard Engine • DoS attack prevention • Traffic segmentation
Operations, Administration, and Maintenance (OAM)	<ul style="list-style-type: none"> • 802.3ah Ethernet Link OAM <ul style="list-style-type: none"> - Supports 802.3ah link layer remote loopback and discovery (System log and SNMP) - 802.3ah D-Link extension: D-link Unidirectional Link Detection (DULD), (System log and SNMP) 	<ul style="list-style-type: none"> • Cable diagnostics
Management	<ul style="list-style-type: none"> • Web-based GUI (IPv4/IPv6) • Command Line Interface (CLI) through Telnet or SSH • Telnet Server/Client (Support IPv4/IPv6) • TFTP client (IPv4) • Command logging • SNMP v1/v2c/v3 • SNMP traps • System log • RMON v1 • LLDP • BootP/DHCP client • DHCP auto-configuration 	<ul style="list-style-type: none"> • Text-editable config file • Trusted host • DHCP relay (IPv4/IPv6) <ul style="list-style-type: none"> - DHCP relay agent/local relay - DHCP relay option 82 • PPPoE Circuit-ID tag insertion • SNTP • LLDP-MED (for PoE models only) • Password encryption • Dual Image • Ping • Traceroute
MIB	<ul style="list-style-type: none"> • RFC1213 MIB II • RFC1065, 1151, 2578 MIB Structure • RFC1493 Bridge MIB • RFC1157, 2573, 2575, 2576 SNMP MIB • RFC3418 SNMPv2 MIB 	<ul style="list-style-type: none"> • RFC1643, 1650, 2665 Ether-like MIB • RFC2674 802.1p MIB • RFC 2233 Interface Group MIB • RFC 2620 RADIUS accounting client MIB
IETF Standard	<ul style="list-style-type: none"> • RFC768 UDP • RFC791 IP • RFC792 ICMPv4 • RFC2463, 4443 ICMPv6 	<ul style="list-style-type: none"> • RFC793 TCP • RFC826 ARP • RFC1321, 2284, 2865, 2716, 3580 Extensible Authentication Protocol (EAP)
IPv6	<ul style="list-style-type: none"> • RFC1981 Path MTU Discovery • RFC2460 IPv6 • RFC2461, 4861 Neighbor Discovery 	<ul style="list-style-type: none"> • RFC2462, 4862 IPv6 Stateless Address Auto-configuration • RFC2893, 4213 IPv4/IPv6 dual stack function

DGS-1210 Series Metro Ethernet Switches

Order Information	
Part Number	Description
DGS-1210-10	8-Port 10/100/1000BASE-T + 2-Port 100/1000 Mbps SFP Ports Metro Ethernet Switch
DGS-1210-10P	8-Port 10/100/1000BASE-T PoE + 2-Port 100/1000 Mbps SFP Ports Metro Ethernet Switch
DGS-1210-10MP	8-Port 10/100/1000BASE-T PoE + 2-Port 100/1000 Mbps SFP Ports Metro Ethernet Switch
DGS-1210-20	16-Port 10/100/1000BASE-T + 4-Port 100/1000 Mbps GbE/SFP Combo Ports Metro Ethernet Switch
DGS-1210-26	24-Port 10/100/1000BASE-T + 2-Port 100/1000 Mbps GbE/SFP Ports Metro Ethernet Switch
DGS-1210-28	24-Port 10/100/1000BASE-T + 4-Port 100/1000 Mbps GbE/SFP Combo Ports Metro Ethernet Switch
DGS-1210-28P	24-Port 10/100/1000BASE-T PoE + 4-Port 100/1000 Mbps GbE/SFP Combo Ports Metro Ethernet Switch
DGS-1210-28MP	24-Port 10/100/1000BASE-T PoE + 4-Port 100/1000 Mbps GbE/SFP Combo Ports Metro Ethernet Switch
DGS-1210-52	48-Port 10/100/1000BASE-T + 4-Port 100/1000 Mbps GbE/SFP Combo Ports Metro Ethernet Switch
DGS-1210-52MP	48-Port 10/100/1000BASE-T PoE + 4-Port 100/1000 Mbps GbE/SFP Combo Ports Metro Ethernet Switch

¹ All Gigabit Ethernet ports of the DGS-1210 Series hardware version R1 switches support up to 6 kV surge protection.

Updated 02/04/2020

Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2020 D-Link Corporation. All rights reserved. E&OE.

D-Link[®]
Building Networks for People