

PATH TO THE FUTURE

МОНИТОРЫ БИЗНЕС И ПРОДУКТИВНОСТЬ

PRO MP245V

PRO MP245V



Picture and logos

SELLING POINTS

- Экран с диагональю 23.8 дюйма: оптимальный размер для работы с программным кодом, проектирования веб-сайтов и других профессиональных задач
- Сертификация эргономичности TÜV: подавление мерцания экрана (Anti-Flicker) и снижение интенсивности синего света (Less Blue Light)
- Частота обновления 100 Гц и время отклика 1мс (MPRT)
- Функция Eye-Q Check: проверка зрения для предотвращения усталости глаз
- Эксклюзивное приложение Display Kit дополнительные функции и настройки, связанные с монитором
- Яркие светлые оттенки и глубокий черный: контрастность монитора составляет 4000:1
- Два интерфейса для подключения к источникам видеосигнала: порты HDMI™ и D-Sub(VGA)
- Обслуживание без инструментов
- Совместимость с VESA-крепежом



- 1. 1х Разъем постоянного тока
- 2. 1x HDMI™ (1.4)
- 3. 1x D-Sub (VGA)
- 4. 1x Headphone-out
- 5. 1x Kensington Lock
- **6.** 1х 5-позиционный навигационный модуль + Кнопка OSD






PRO MP245V

PRO MP245V

SPECIFICATION

	EAN	4711377121965
Barcode Info	UPC	824142332351
	UCC14	10824142332358
Model	Part No	9S6-3PC0CM-014
	MKT Name	PRO MP245V
	MKT Spec	PRO MP245V
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60cm)
	Active Display Area (mm)	527(H) x 296 (V)
	Curvature	Flat
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	30~160 KHz(H) / 60~144 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	N/A
	NTSC (CIE1931 area percentage/overlap)	N/A
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
	Rec.2020 (CIE1970 area percentage/overlap)	N/A
		16.7M
	Display Colors Color bit	8 bits
	Note_HDMI™	1920 X 1080 (Up to 100Hz)
	Note_DVI	N/A
I/O Ports	HDMI™	1
	HDMI [™] version	1.4b
	HDMI™ HDCP version	1.4
	D-Sub	1
	Headphone-out	1
	Lock type	Kensington Lock
I/O Ports (Rear)	Card Reader	N/A
	Annual Energy Consumption (KWh)	N/A
Power	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	E
	Adapter's KC safety Number	N/A
	Power Cord Type	C13
	QC Output Power	N/A
	PD Output Power	N/A





PRO MP245V

PRO MP245V

PRO MP245V		
	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
In The Box	USB Type C to Type C Cable	0
20.	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	N/A
	Product Dimension with Stand (WxDxH) (mm)	N/A
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (inch)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (inch)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (inch)	N/A
	Inside Carton Dimension (WxDxH) (inch)	N/A
Dimension & Weight	Weight (Net kg)	N/A
Dimension & Weight	Weight (Net kg) Weight (Gross kg)	N/A
Weight	Weight (Gloss kg) Weight Without Stand (kg)	N/A
Warranty	Warranty	12M
vvarianty	warranty	14411