



## X-Flow Type F 5W-30 Semi Synthetic

**Recommended by Comma for applications requiring:**

ACEA A5/B5  
API SL/CF

### Product Features:

- Semi synthetic 5W-30 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

### Typical Inspection Data:

Density @ 20°C	0.852 g/cm <sup>3</sup>
Viscosity @ 100°C	10.4 cSt
Viscosity @ 40°C	58 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	4600 cP
T.B.N.	8.1 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.11%
Calcium	0.32%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

UPDATED: 03.05.2019

**Moove Lubricants Ltd.** Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: [sales@commaoil.com](mailto:sales@commaoil.com) [www.CommaOil.com](http://www.CommaOil.com)