



Quality is in our nature

ПРОДУКЦИИ

Июнь 2016



EUROL MTF 75W-80 GL5

Synthetic transmission oil suitable for certain manual gearboxes

Eurol® MTF 75W-80 GL-5 is a synthetic gear oil, which can be used in final drives and manual transmissions (where GL-5 quality is required).

Eurol® MTF 75W-80 GL-5 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol® MTF 75W-80 GL-5 has an excellent high load carrying capacity for an excellent absorption of sudden peak loads. The viscosity decrease due to heavy loads is only slightly, which will extend oil drain intervals (and in some cases lifetime filling) and ensures proper viscosity.

Eurol® MTF 75W-80 GL-5 contains special friction modifiers, which ensure sustainable fuel saving and less heat development.

Eurol® MTF 75W-80 GL-5 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Eurol® MTF 75W-80 GL-5 is compatible with most elastomers and seal materials and does not foam under extreme loads.

ПРОИЗВОДИТЕЛЬНОСТЬ

API GL-5
MIL-L-2105-D
ALFA ROMEO
BMW 2300 1434 404
BMW 2300 7533 513
BMW 2300 7533 818
CITROEN
FIAT
FORD M2C200-C/C2/C3
LANCIA

OPEL 19 40 182
OPEL 19 40 757
OPEL 19 40 768
OPEL 19 40 776
PEUGEOT
RENAULT
VOLVO 97308
VW 501 50 (G 005 000 05 / G 005 000 / G 005 000 20 / G 052 911 A1/A2)
VW TL 521 71 (G 052 171 A1/A2)

Конкретные значения

		75W-80
Density 20°C	Kg/L	0,879
Viscosity 100°C	cSt	9,4
Viscosity 40°C	cSt	49,8
Viscosity Index		175
Flash point COC	°C	>190
Pour point	°C	<-45

Доступные объемы

E110080 - 1L, E110080 - 60L



Содержание этого документа имеет целью дать возможность читателю ознакомиться со свойствами и возможности применения Eurol продукции. Информация, содержащаяся в данном документе в любое время и без уведомления изменять в связи с постоянным развитием продукта. Аналитические данные в данной спецификации являются типовыми. Малые отклонения, которые могут возникнуть во время нормального процесса производства продукта, качество продукта это не влияет. Хотя этот текст с большой тщательностью, компилятор не несет ответственности за ущерб в результате бездействия и / или неточностей в тексте. Читателю рекомендуется сделать конечный продукт в консультации с поставщиком.

EUROL BV ENERGIESTRAAT 12 NIJVERDAL THE NETHERLANDS TEL. +31 (0)548 61 51 65 EUROL.COM