

V-belt spray

For extending the service life of V-belts

- Prevents slipping, transfers full drive output, eliminates squeaking
- Eliminates readjustment work in case of minor belt slippage due to cold, moisture or due to normal elongation
- AOX-free

Contents	400 ml
Chemical basis	Mineral oil
Colour	Light yellow
Boiling point	-44 °C
Ignition temperature	250 °C
Shelf life from production	24 Month



Art. no. 0893 230

P. Qty.: 1 / 12

Details/Application

For V-belts made from leather, rubber, balata, hair etc. Not suitable for use on flat belts. When using V-belt spray, contact with the belt pulleys is increased – separation and friction problems are reduced to a minimum. The efficiency of the V-belt is increased.

Instructions

Fit the spray head and spray along the belt with the end of the spray tube close to inside of the belt. Or spray on an area inside with the engine running for approx. 5 seconds.

Clean running surfaces before initial use. Use sparingly and precisely – avoid excess material.

Notice

Only use in well-ventilated areas.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.