

Lubricating grease WGF 130

High-performance lubricating grease

- Lithium-soap grease with molybdenum sulphide (MoS₂)
- Forms a solid lubricating film on the running surfaces under load from the grease itself
- Significantly improves run-in conditions
- Ensures additional emergency running lubrication
- Reduces friction and thus prevents excessive wear
- Extends lubricating period
- Protects against corrosion
- Resistant to water
- Temperature resistant from -30°C to +130°C, briefly up to +150°C
- Colour: Black
- Consistency as per NLGI: 2



Contents	1 l
Chemical basis	Lithium 12 hydroxystearate
Oil basis	Mineral oil
Colour	Black
Min./max. temperature resistance	-30 to 130 °C
Max. short-term temperature resistance	150 °C
Shelf life from production	36 Month

Art. no. 0893 530

P. Qty.: 1 / 6

Details/Application

The high-performance grease can be used to lubricate all kinds of roller and friction bearings (e.g. wheel bearings), guides, joints, splined shafts, threaded spindles as well as bearings with extremely high surface pressures or impact loads.

Instructions

Clean and degrease the parts to be lubricated. Then apply the grease in the required coating thickness.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.