



## EP80W-90 GL-4 Mineral

### Product Features:

- Extreme pressure gear oil for manual gearboxes.
- Recommended by Comma for applications requiring an 80W-90 or 85W-90 API GL-4 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

### Typical Inspection Data:

Density @ 20 °C	0.875 g/cm <sup>3</sup>
Viscosity @ 100 °C	14.0 cSt
Viscosity @ 40 °C	132 cSt
Phosphorus	0.01%
Colour	Brown
Pour Point	-30 °C

### Performance Profile:

Recommended by Comma for certain applications where an 80W-90 or 85W-90 API GL-4 oil is specified Suitable for use where the following specifications are called for:

<b>API GL-4</b>	<b>API GL-3</b>
<b>Ford SQ-M2C9008-A</b>	<b>MB 235.1</b>

30-11-2017