



### Physical Properties:

Appearance	hydrocarbon odour
------------	-------------------

## Carb Clean

### Product Features:

- A powerful blended solvent specifically designed for removing spent fuel deposits.
- Easily dissolves oils, greases, gums and carbon deposits from fuel delivery areas.

### Direction of use:

1. Ensure engine is cold & switched off.
2. Remove air cleaner/ filter.
3. Shake can & (with extension tube fitted) apply liberally to exterior of carburettor & linkages. Allow to soak & repeat as necessary.
4. Start engine & spray inside carburettor throat.
5. Switch off ignition & refit air cleaner/ filter. For Automatic Choke spray both ends of choke valve & vacuum cylinder. Important – Wash off immediately if sprayed on paintwork – may cause streaking.

### Handling:

- Caution pressurized container: protect from sunlight and other heat sources.
- Refer to Material Safety Data Sheet.

### Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified as follows; first letter denotes the year (letter for 2019 is M), second letter denotes the month (letter for August is H), numbers denote the day of the month. For example: MH13 = 13th August 2019, NA26 = 26th January 2020.

UPDATED: 03-09-2019

**Moove Lubricants Ltd.** Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com [www.CommaOil.com](http://www.CommaOil.com)