



Typical Inspection Data:

Colour	Amber
Texture	Smooth
NLGI	2 (Medium)
Worked Penetration @ 25 °C	280 mm10 ⁻¹
Drop Point	200°C
Operating Temperature Range	-10 °C to +120 °C
Oil Separation (168 hrs @ 40 °C)	<7%
Copper Corrosion (24 hrs @ 100 °C)	1a
Water Washout @ 38 °C	<7%

Multipurpose Lithium Grease

Product Features:

- Lithium-based grease with good temperature tolerance. Suitable for hubs, universal joints, chassis and general greasing.
- Long life for use in well-sealed bearings.
- Oxidation inhibited – Ensures long life in storage.
- Good water resistance – Provides satisfactory lubrication in the presence of water and is not washed out of bearings.
- Good corrosion protection – Rust inhibited to protect bearing surfaces.

Handling:

- Never over pack the bearing.
- It is sound lubrication practice to remove the old grease before a new grease is introduced.
- If used grease cannot be removed, Comma Multipurpose grease is generally compatible with other lithium greases.
- When mixed with other grease types, this grease should be satisfactory below an operating temperature of 80 °C.
- Avoid extremes of temperature.
- Store under cover.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.

28-02-2017