

Technical Data Sheet



Typical Inspection Data:

Density @ 20 °C	0.875 g/cm³
Viscosity @ 100 °C	14.0 cSt
Viscosity @ 40 °C	132 cSt
Phosphorus	0.01%
Colour	Brown
Pour Point	-30 °C

Performance Profile:

Recommended by Comma for certain applications where an 80W-90 or 85W-90 API GL-4 oil is specified Suitable for use where the following specifications are called for:

API GL-4	API GL-3
Ford SQ-M2C9008-A	MB 235.1

EP80W-90 GL-4

Mineral

Product Features:

- Extreme pressure gear oil for manual gearboxes.
- Recommended by Comma for applications requiring an 80W-90 or 85W-90 API GL-4 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

30-11-2017

Tel: +44 (0)1474 564311, Fax: +44 (0)1474 333000 Email: salesi@commaoil.com www.CommaOil.com