

Multi-purpose grease construction/agriculture

EP-2 grease with a lithium/calcium base

- Resistant to high pressure due to EP additive
- High shearing strength
- High resistance to weathering
- High resistance to water and steam

Soap base	Lithium/calcium
Min./max. temperature conditions	-30 to 120 °C
Colour	Blue
NLGI grade/conditions	2/with DIN 51818
Base oil viscosity, kinematic/conditions	300 mm ² /s/at 40 °C
Min./max. worked penetration/conditions	265 x 0.1 mm-295 x 0.1 mm/in accordance with DIN ISO 2137
Corrosion protection period/category	Corrosion category 0-0
VKA welding load	3400 N
Shelf life from production	48 Month
Oil basis	Mineral oil



Weight of content	Container	Lubricant code	Art. No.	P. Qty.
25 kg	Pail	KP2K-30	0893 874 103	1
400 g	Cartridge	KP2N-30	0893 874 1	1/12
400 g	Cartridge Lube Shuttle	KP2K-30	0893 874 400	1/12
500 g	Screwed cartridge	KP2K-30	0893 874 102	1/12

Details/Application

Particularly suitable for heavily loaded devices and machines, such as construction and agricultural machinery. The operational area covers a wide range of applications such as heavily loaded roller bearings and ball bearings, work roll bearings and support roller bearings, hot and cold shear systems, roller bearings and plain bearings, etc. Ideal for use even in extremely unfavourable conditions, such as with wetness, vapour, dust, mud and under extreme weather conditions.



Notice

Greases are supplied in plastic cartridges. The plastic cartridges improve storage (they prevent the grease from oozing out at high temperature). Store cartridges upright in a cool, dry place! The operating instructions of the vehicle, machinery and assembly manufacturers must be observed!